

CVC™ CURE RS Concrete Curing Material

Product Description	High level of resin and solvent based liquid curing material which prevents water loss of fresh concrete by being applied to new poured concrete surfaces by means of roller or by spraying method.	
Product Number	104-2	
Areas of Application	 Internal and external field concretes, Concretes of airports, highways and bridges, Ports, storage fields, Apron and parking fields, Retaining walls, columns and girders, terrace roofs, It is suitable for all concrete surfaces such as glazed concrete applications, surface hardeners etc. 	
Product Advantages	 It is economical; eliminates expensive methods such as watering and similar methods, Ensure to reach planned strengths, It increases the strength of concrete against outdoors weather conditions (sun, frost etc.), Increases wear resistance of the surface, Decrease the possibility of shrinking cracks thanks to high curing, 	
Technical Data	Appearance	Transparent liquid
	Drying time	30-45 minutes (variable depending on environmental conditions)
	Consumption	100-150 gr/m ² depending on the environment conditions
	Application Equipment Danger class	Sponge roller, brush or a mechanical pulverizator Flammable
Application	It is started to applied when the brightness on the surface of fresh poured concrete is tarnished (when the free water is disappeared). It should be applied right after the formworks are removed on the application with formwork. Application may be carried out by means of roller, brush or spraying method. After the application, the surface of concrete which is applied CVC CURE RS should be protected against rain and similar factors for 3-5 hours.	
Storage	For 12 months in a cool and dry environment, without opening its original package. Keep away from direct sunlight and overheated environment.	



