

## **CVC™ RA** **Stamped Concrete Mold Separator**

<b>Product Description</b>	This product is used in stamped concrete applications in order to avoid the molds from sticking to the surface. It is in powder form, and also it gives the stamped concrete an aged look with desired colors.	
<b>Product Number</b>	1003	
<b>Areas of Application</b>	This product is used in all stamped concrete applications.	
<b>Product Advantages</b>	<ul style="list-style-type: none"> <li>• Avoids all surface hardeners from sticking to the molds,</li> <li>• Avoids wear on molds,</li> <li>• Gives an aged, and decorative look, and comes in desired colors,</li> <li>• Allows all mold designs to have a great print.</li> </ul>	
<b>Technical Data</b>	Color	Grey, and all desired colors
	Form	In the form of micronized powder
	Packaging	20 kg buckets
	Consumption	Approximately 0.200-0.300 kg/m <sup>2</sup>
	Cleaning	Clean all tools with water
	Storage	In cool and dry environments the shelf life is up to 12 months
	Caution	It is not flammable. Due to its micronized form do not inhale, and keep clear from eyes
<b>Application</b>	After using <b>CVC SC Stamped Concrete</b> (on soft when pressed with finger but not wet surface) <b>CVC RA</b> (stamped concrete mold separator) is scattered on to the surface, and with the molds the stamping process will commence. The scattering process should be in the direction of the wind, and parallel to the surface. This process must be done at the thinnest possible way and piling should be avoided.	